

1 AUG 1943

MR April 1943

~~SECRET~~  
*Republic*  
*P-49B/H*

NATIONAL ADVISORY COMMITTEE FOR AERONAUTICS

# WARTIME REPORT

ORIGINALLY ISSUED  
April 1943 as  
Memorandum Report

VIBRATION SURVEYS OF THE P-47-B RUDDER

AND FIN-RUDDER ASSEMBLY

By Theodore Theodorsen and Arthur A. Regier

Langley Memorial Aeronautical Laboratory  
Langley Field, Va.

# NACA

WASHINGTON

NACA REPORT  
L-653  
Langley Field, Va.

NACA WARTIME REPORTS are reprints of papers originally issued to provide rapid distribution of advance research results to an authorized group requiring them for the war effort. They were previously held under a security status but are now unclassified. Some of these reports were not technically edited. All have been reproduced without change in order to expedite general distribution.

L - 653



3 1176 01403 5340

MEMORANDUM REPORT

for the

Army Air Forces, Materiel Command

## VIBRATION SURVEYS OF THE P-47-B RUDDER

## AND FIN-RUDDER ASSEMBLY

By Theodore Theodorsen and Arthur A. Regier

The present work was conducted in connection with a study of the flutter characteristics of the P-47 tail assembly. The original fabric-covered rudder designated by "I" was subsequently replaced by a metal-covered rudder designated by "II." The fin was also somewhat reinforced and the vibration results on the combination of this reinforced fin and the metal rudder is given under III. This combination, which is now in use (April 1943), proved completely satisfactory from a vibration standpoint and has subsequently been tested in flight to a true speed of the order of 600 miles per hour. As a matter of record the vibration survey is therefore given.

In these surveys, note that some tests were conducted with the tab link rigidly fastened to the center hinge post; some with the tab free. The rudder was tested suspended on a low-frequency rubber mounting, thus being in a "floating" condition. The fin-rudder unit was tested with the base of the rudder solidly fixed to a heavy base support,

In each figure the plus and minus sign designates opposite phases of the amplitude and the size of the sign, the approximate amplitude on an arbitrary but relatively correct scale. Nodal lines are drawn in some of the figures. The designation of each response mode is as usual a matter of conjecture. The figures are otherwise self-explanatory. It is hoped these may serve as a standard of comparison for new designs of high-speed rudder assemblies.

I. Fabric Rudder without Fin:

<u>Sketch</u>	<u>Cycles per second</u>	<u>Remarks</u>
A	33	Tab locked, driver at light as shown. Mainly bending - two nodal lines.
B	48	Bending plus substantial torsion, two nodal lines.
C	77	Mainly bending, some torsion present, three nodal lines.
D	108	Mainly bending, three nodal lines.
E	135	Apparently four nodal lines present
F	103	Driver placed as shown; mainly bending plus tip torsion, three nodal lines.
G	121	Mainly bending plus more of the tip torsion, three nodal lines.
H	143	Much torsion present, three (or four) nodal lines.
I	247	High-order bending torsion, seven or eight nodal lines.


II. All-Metal Rudder without Fin:

<u>Sketch</u>	<u>Cycles per second</u>	<u>Remarks</u>
A	47	Tab fast, driver placed as shown; bending plus tab in phase; two nodal lines.
B	57	Bending plus tab out of phase; two nodal lines.
C	85	Coupled torsion and bending, two nodal lines.
D	100	Bending, three nodal lines.
E	128	Mainly bending plus tip torsion, three nodal lines.
F	161	Mainly bending plus slight tip torsion, four nodal lines.
G	50	Tab free, mainly bending; small tab movement out of phase, two nodal lines.

III. All-Metal Rudder with Reinforced Metal Fin:

<u>Sketch</u>	<u>Cycles per second</u>	<u>Remarks</u>
A	17	
B	50	
C	64	
D	74	

Langley Memorial Aeronautical Laboratory,  
National Advisory Committee for Aeronautics,  
Langley Field, Va., April 28, 1943.



**I. NEW FABRIC RUDDER NO. 89R54000 FOR P-47-B AIRPLANE**

Weight..... 47.5 pounds

Balance..... 1 inch-pound over balance

Center of gravity..... 4 feet 9.1 inches from top  
2 feet 6.6 inches from bottom

Maximum dimensions..... 7 feet 3.7 inches by 2 feet  
3.5 inches

Hinge line about 4 inches back from leading edge.

Natural frequencies, suspended in rubber and tab locked to center hinge post:

Cycles per second - 33, 48, 77, 108, 135, 103, 121,  
143, 247

Rudder similar to this failed in the 8-foot high-speed tunnel at 460 miles per hour. Predominant frequency at failure about 140 cycles per second. Top part of rudder failed, fabric ripped, trailing edge gone.



New Fabric Rudder - 89R5400  
Suspended in Rubber

33~

Tab Fast

48~

Sept. 8, 1942





New Fabric Rudder  
Suspended in Rubber  
Tab Fast

89 R 54000

Sept. 9, 1942

77v

108v




New Fabric Rudder  
Suspended in Rubber

89 R 54000

Tab tight to center hinge post.

Sept. 10, 1942

135~






New Fabric Rudder  
Suspended in Rubber  
Tab Fast

89 R 54000


Sept. 10, 1942

103 ~



F

143 ~



H



New Fabric Rudder- 89 R 5400  
Suspended in Rubber


121~

Tab Fast

247~

Sept. 10, 1942





## II. NEW ALL-METAL RUDDER NO..93R54500 FOR P-47-B AIRPLANE

Weight..... 42 pounds

Balance..... 22 inch-pounds under  
balance

Center of gravity..... 4 feet 1.9 inches from  
top  
3 feet 1.2 inches from  
bottom

Maximum dimensions..... 7 feet 3 inches by 2 feet  
6 inches

Hinge line about 4.5 inches from leading edge near tip  
5.5 inches from leading edge near root

Radius of gyration about hinge line. 7.1 inches

Natural frequencies, suspended in rubber and tab locked to  
center hinge post, driver at light:

47, 57, 85, 100, 128, 161 cycles per second

Natural frequencies, suspended in rubber and tab loose:

50,


All-Metal Rudder 93R54500

Suspended in Rubber:


Sept. 10, 1942

47 ~ Tab Locked

57 ~



A



B


All-Metal Rudder 93R54500

Suspended in Rubber

Sept 10, 1942


Tab Locked

85 ~



C

100 ~



D

← Driver

← Driver

Tab Tight

All-Metal Rudder 93R54500


Suspended in Rubber

Sept 10, 1942


Tab Locked

128~

161~



Driver



Driver

Tab Tight


All Metal Rudder

93 R 54500

Tab Loose

Sept. 10, 1942

50 N



G

III. REINFORCED METAL FIN AND ALL-METAL RUDDER FOR  
P-47B AIRPLANE

Fin Data

Part No. 89J55000, 3896

Weight..... 47 pounds  
Maximum height..... 66 inches  
Maximum length..... 49 inches  
Maximum thickness..... 5.5 inches

Rudder Data

Part No. 93R54500, MFG 9-42

Weight..... 42 pounds  
Maximum height..... 87 inches  
Maximum chord..... 29 inches

Natural frequencies of assembly  
as mounted on stand in sound laboratory:

17, 50, 64, 74




All Metal Rudder

93 R 54500

17~

Sept. 17, 1942




A

All Metal Rudder

93 R 54500

50 ~

Sept. 16, 1942




B

All Metal Rudder

93 R 54500

64 ~.

Sept. 16, 1942




C

All Metal Rudder


93 R 54500

Sept. 16, 1942

74 2



D



P-47-B rudder and fin-rudder assembly.

NATIONAL ADVISORY COMMITTEE FOR AERONAUTICS  
LANGLEY MEMORIAL AERONAUTICAL LABORATORY - LANGLEY FIELD, VA.

NASA Technical Library



3 1176 01403 5340

